## **AWTA Product Testing**

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client: Materialised Pty Ltd

19 Heath Road

Blakehurst NSW 2221

18-001991 Test Number :

**Issue Date** 2/05/2018 **Print Date** 20/01/2020

"Crypton George" **Sample Description** Clients Ref:

Backed woven upholstery fabric

Off White Colour: End Use: Upholstery

100% Polyester with backing Nominal Composition: 525g/m2 Nominal Mass per Unit Area/Density:

Nominal Thickness: Approx: 1mm

AS/NZS 1530.3-1999 Methods for Fire Tests on Building Materials, Components and Structures

> Part 3: Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release

Face tested: Face

Date tested: 02/05/2018

Standard Error Mean Ignition time 0.29 8 31 min Flame propagation time Nil Nil sec Heat release integral 3.6 93.6 kJ/m²

Smoke release, log d 0.0328 -0.7626

Optical density, d 0.1751 / metre

Number of specimens ignited: 6 Number of specimens tested: 6

Regulatory Indices:

Ignitability Index Range 0-20 Spread of Flame Index Range 0-10 Heat Evolved Index Range 0-10 Smoke Developed Index Range 0-10

191456 27031 Page 1 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing

Mechanical Testing

Performance & Approvals Testing

: Accreditation No Accreditation No

· Accreditation No. 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



983

A. JACKSON B.Sc.(Hons)

APPROVED SIGNATORY

## **AWTA Product Testing**

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client: Materialised Pty Ltd

19 Heath Road

Blakehurst NSW 2221

18-001991 Test Number :

**Issue Date** 2/05/2018

20/01/2020 **Print Date** 

The reaction of thin unsupported flexible materials to flame impingement can be assessed in accordance with AS 1530.2. Where materials of thickness less than 2 mm that are sufficiently flexible to be bent by hand around a mandrel of 2mm diameter or less are subjected to the test described herein, they should also be subjected to the test in AS 1530.2.

Each test specimen had an unattached backing of 4.5mm thick fibre reinforced cement board.

The specimens melted and flowed away from the area of maximum heat during the test. Due to this phenomena it should be recognised that this test result may not be a true indication of the product's fire hazard properties.

Each test specimen was restrained on the exposed face by a layer of galvanised welded square mesh made from wire of nominal diameter 0.8mm and nominal spacing 12mm in both directions and securely fixed to a backing board at four points each 100mm from the centre of the sample and the assembly clamped in four places.

To allow free movement of sample during testing all corners were folded away from the clamps.

These results only apply to the specimen mounted, as described in this report. The result of this fire test may be used to directly assess fire hazard, but it should be recognised that a single test method will not provide a full assessment of fire hazard under all fire conditions.

191456 27031 Page 2 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



the Managing Director of AWTA Ltd.

Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing

relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by

Mechanical Testing

Performance & Approvals Testing

: Accreditation No

Accreditation No.

983 1356

· Accreditation No. Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results



APPROVED SIGNATORY

A. JACKSON B.Sc.(Hons)